

## **AXIS Camera Station S2212 Appliance**

## All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2212 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2212 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 12 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2212 provides a reliable surveillance solution.

- > All-in-one solution with integrated PoE switch
- > High-definition surveillance with up to 4K resolution
- > AXIS Camera Station licenses included
- > Full compatibility with Axis products



www.cxis.com T10136415/EN/M6.2/2105

	AXIS Camera Statio	on S2212 A	Appliance
Licenses	12 AXIS Camera Station core licenses included, can be upgraded with additional licenses (sold separately)		Up to 12 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 12 video channels and 24 doors		
Hardware		Recording	Qualified for recording up to 12 video channels with a total
Processor	Intel® Core™ i3		recording rate up to 192 Mbit per second
Memory	8 GB	General	
Storage	Surveillance Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 6 TB (1x6 TB)	Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD
Switch	Op	Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)
Graphic card	Intel® HD Graphics	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Power	Max 270 W, 135 W PoE dedicated 100 - 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter	CNS EN 6 FCC KC k Safe IEC/	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
Connectors	Front side:  1x USB 3.0  1x Audio line in  1x Audio line out  Rear side Switch:  12x PoE ports 10/100 Mbps  1x SFP 10/100/1000 Mbps  1x RJ45 10/100/1000 Mbps  Rear side Server:  1x RJ45 10/100/1000 Mbps  2x USB 2.0  1 Displayport™  1 HDMI port		
		Dimensions	330 x 230 x 78 mm (13 x 9.1 x 3.1 in)
		Weight	5.8 kg (12.8 lb)
		Included accessories	Rack ears, power adapter
		Optional accessories	Surveillance Hard Drive 6 TB available from Axis AXIS TS2901 Appliance Stand Axis desktop terminals Axis Ethernet surge protector
Video			For more accessories, see axis.com
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p	Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty

## **AXIS Camera Station**

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on *axis.com* 

Environmental responsibility: axis.com/environmental-responsibility

