SIEMENS

Data sheet 6EP3321-6SB10-0AY0

LOGO!Power/1AC/15VDC/1.9A

LOGO!Power 15 V / 1.9 A stabilized power supply input: 100-240 V AC output: 15 V DC / 1.9 A *Ex approval no longer available*

Input	
Input	1-phase AC or DC
Rated voltage value Vin rated	100 ... 240 V
Voltage range AC	85 ... 264 V
input voltage	
● at DC	110 ... 300 V
Wide-range input	Yes
Overvoltage resistance	300 V AC for 1 s
Mains buffering	at Vin = 187 V
Mains buffering at Iout rated, min.	40 ms; at Vin = 187 V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
● at rated input voltage 120 V	0.63 A
● at rated input voltage 230 V	0.33 A
Switch-on current limiting (+25 °C), max.	25 A
I^2t, max.	0.8 $A^2 \cdot s$
Built-in incoming fuse	internal
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 6 A characteristic B or from 2 A characteristic C

Output	
Output	Controlled, isolated DC voltage
Rated voltage Vout DC	15 V
● output voltage at output 1 at DC rated value	15 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	200 mV
Residual ripple peak-peak, typ.	30 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	300 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	50 mV
Adjustment range	10.5 ... 16.1 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for output voltage OK
On/off behavior	No overshoot of Vout (soft start)
Startup delay, max.	0.5 s
Voltage rise, typ.	100 ms

Subject to change without notice
© Copyright Siemens

Rated current value Iout rated	1.9 A
Current range	0 ... 1.9 A
● Note	+55 ... +70 °C: Derating 2%/K
supplied active power typical	28.5 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
Efficiency	
Efficiency at Vout rated, Iout rated, approx.	83 %
Power loss at Vout rated, Iout rated, approx.	6 W
power loss [W] during no-load operation maximum	0.3 W
Closed-loop control	
Dynamic mains compensation (Vin rated ±15 %), max.	0.2 %
Dynamic load smoothing (Iout: 10/90/10 %), Uout ± typ.	2 %
Load step setting time 10 to 90%, typ.	1 ms
Load step setting time 90 to 10%, typ.	1 ms
Protection and monitoring	
Output overvoltage protection	Yes, according to EN 60950-1
Current limitation, typ.	2.5 A
property of the output short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
enduring short circuit current RMS value	
● maximum	2.5 A
overcurrent overload capability in normal operation	overload capability 150% Iout rated typ. 200 ms
Overload/short-circuit indicator	-
measuring point for output current	50 mV =^ 1.9 A
overcurrent overload capability when switching on	150% Iout rated typ. 200 ms
Safety	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
Protection class	Class II (without protective conductor)
Degree of protection (EN 60529)	IP20
Approvals	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus-Recognized (UL 60950, CSA C22.2 No. 60950), File E151273, NEC class 2 (acc. to UL 1310)
certificate of suitability NEC Class 2	Yes
CB approval	Yes
certificate of suitability EAC approval	Yes
Marine approval	ABS, BV, DNV GL, LRS
EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	not applicable
Noise immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
● during operation	-25 ... +70 °C
— Note	with natural convection
● during transport	-40 ... +85 °C
● during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 … 95% no condensation
Mechanics	
Connection technology	screw-type terminals
Connections	
● Supply input	L, N: 1 screw terminal each for 0.5 ... 2.5 mm2 single-core/finely stranded
● Output	+, -: 1 screw terminal each for 0.5 ... 2.5 mm²
● Auxiliary	-
width of the enclosure	36 mm

Subject to change without notice
© Copyright Siemens

height of the enclosure	90 mm
depth of the enclosure	53 mm
required spacing	
● top	20 mm
● bottom	20 mm
● left	0 mm
● right	0 mm
Weight, approx.	0.12 kg
product feature of the enclosure housing can be lined up	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15, direct mounting in different mounting positions
MTBF at 40 °C	2 938 542 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

Subject to change without notice
© Copyright Siemens