## UHD35x

Bright, True 4K UHD gaming and home entertainment projector







- True 4K UHD resolution HDR and HLG compatible
- Lights on viewing 3600 lumens for use any time of day
- Lightning fast gaming projector Delivers 1080p 240Hz with an ultra-low input lag of 4.2ms
- Full 3D compatible Experience life-like bigscreen entertainment



Immerse yourself in a world of Ultra HD gaming, live sports, TV shows and movies. The lightning-fast, low latency 4K UHD UHD35x delivers impressive cinema-quality images, an ultra-low input lag of 4.2ms and a high refresh rate of 240Hz - perfect for a competitive gaming advantage.

TV and movie fans can also enjoy excellent colour depth, crystal clear detail, and sparkling contrast for a stunningly immersive experience.

## **Specifications**

EAN: 5055387666184, Colour: White	
Display/image	DIDTU
Display technology	
Resolution	UHD (3840x2160)
Brightness	3,600 lumens
Contrast ratio	1,000,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - norizontal	+/-40°
Keystone correction - vertical	+/-40°
Horizontal scan rate	31 ~ 135Khz
/ertical scan rate	24 ~ 120Hz
Uniformity	80%
Screen size	0.84m ~ 7.62m (33" ~ 300") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	
Throw ratio	1.5:1 ~ 1.66:1
Projection distance (m)	1.21m - 9.9m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	15.84 mm~17.42mm/0.624"~0.686"
_ens shift	Vertical +0%
Native offset	105%
Connectivity	10070
Connections	Innute 2 × HDML2 0
	Inputs 2 x HDMI 2.0
	<b>Outputs</b> 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A
	<b>Control</b> 1 x RS232, 1 x 12V trigger
General	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
BD compatibility	1080p(50/60Hz), 2160p(50/60Hz)
3D compatibility 3D	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60
3D compatibility 3D Security	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D
3D compatibility 3D Security OSD / display languages	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese,
BD compatibility BD Security DSD / display languages Operating conditions	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max
BD compatibility BD Security OSD / display languages Operating conditions Remote control	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote
2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 10W
3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1
3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 10W AC power cord Remote control 2x AAA batteries
D compatibility D becurity DSD / display languages Operating conditions Remote control Speaker count Vatts per speaker	1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 10W AC power cord Remote control

Input lag	2x AAA batteries Basic user manual 4.20ms		
		Power	
		Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W		
Power consumption (min)	220W		
Power consumption (max)	305W		
Weight and dimensions			
Dimensions (W x D x H) mm	315 x 270 x 118		
Gross weight	4.68 kg		
Net weight	3.98 kg		







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 11012023022312