

UHD55

Smart 4K UHD home entertainment projector









- 4K UHD resolution with HDR and HLG High Brightness 3600 lumens with 3xHDMI 2.0
- Wide color gamut with 97% coverage via DCI-P3
 Active Shutter PureMotion MEMC delivers judder free motion video
- 4K gaming with lightning-quick input lag at 16ms -3x3 Warping delivers geometric correction for image correction and alignment
- Alexa Smart Home and Google Action (Home)
 Digital Assistant Voice Control Optoma
 Marketplace featuring Streaming Apps



Prepare to be amazed. Immerse yourself in a world of Ultra HD gaming, live sport, TV shows and movies with the UHD55 high brightness projector. Experience sharp 4K UHD resolution and ultra-low input lag for smooth high framerate gaming. TV and movie fans can enjoy mesmerising entertainment on an expansive screen with super-wide DCI-P3 cinematic colour, crystal clear detail, and sparkling contrast.

Specifications

opoomoationo	
Display/image	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	3,600 lumens
Contrast ratio	1,200,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3 +/-40°
Keystone correction - horizontal	+/-40
Keystone correction - vertical	+/-40°
Displayable colours (millions)	1073.4
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.87m ~ 7.68m (34.1" ~ 302.4") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical Throw ratio	1.21:1 ~ 1.59:1
Projection distance (m)	1.2m - 8.1m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	12.81 ~ 16.74
Lens shift	Vertical +10%
Native offset	105%
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio
	3.5mm
	Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A
	Control 2 x USB-A reader/wireless, 1 x RS232, 1 x 12V trigger, 1 x RJ45
Wireless - technology	IEEE 802.11 a/b/g/n
Wireless - security	WEP, TKIP, AES, WPA, WPA2
Wireless - antenna	Omnidirectional
Wireless - antenna Wireless - operating frequency	Omnidirectional 2.4GHz
Wireless - operating frequency General	2.4GHz
Wireless - operating frequency General Noise level (typical)	2.4GHz 26dB
Wireless - operating frequency General Noise level (typical) Noise level (max)	2.4GHz 26dB 28dB
Wireless - operating frequency General Noise level (typical)	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA,
Wireless - operating frequency General Noise level (typical) Noise level (max)	2.4GHz 26dB 28dB
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz),
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility Security OSD / display languages	26dB 28dB UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility Security	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility Security OSD / display languages	26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control	26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count	26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/ip, 576/ip, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/ip, 576/ip, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - antenna	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - antenna Wireless - operating frequency	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - antenna Wireless - operating frequency Power	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/ip, 576/ip, 720p/50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional 2.4GHz
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - antenna Wireless - operating frequency Power Power	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/ip, 576/ip, 720p/50/60Hz), 1080l(50/60Hz), 1080p/50/60Hz), 2160p/50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional 2.4GHz
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - antenna Wireless - operating frequency Power Power Supply Power consumption (standby)	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480//p, 576i/p, 720p/50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional 2.4GHz 100 ~ 240V, 50 ~ 60Hz 0.5W
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - antenna Wireless - operating frequency Power Power Power supply Power consumption (standby) Power consumption (min)	26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional 2.4GHz 100 ~ 240V, 50 ~ 60Hz 0.5W 220W
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Networking Wireless - attenna Wireless - operating frequency Power Power Power supply Power consumption (min) Power consumption (max)	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480//p, 576i/p, 720p/50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional 2.4GHz 100 ~ 240V, 50 ~ 60Hz 0.5W
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3	26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional 2.4GHz 100 ~ 240V, 50 ~ 60Hz 0.5W 220W
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Networking Wireless - technology Wireless - antenna Wireless - operating frequency Power Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional 2.4GHz 100 ~ 240V, 50 ~ 60Hz 0.5W 220W 320W
Wireless - operating frequency General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3	2.4GHz 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480/p, 576/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord Remote control inc CR2025 battery Quick start user manual WUSB wireless adapter 4.40ms IEEE 802.11 a/b/g/n Omnidirectional 2.4GHz 100 ~ 240V, 50 ~ 60Hz 0.5W 220W 320W





