

## Product data sheet

### Characteristics

# AP8659

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 20A/208V, 16A/230V, (21) C13 & (3) C19



### General

Provided equipment	CAN port terminator Installation guide Rack mounting brackets Safety guide Serial configuration cable
--------------------	---

### Physical

Colour	Black
Depth	5.1 cm
Height	182.9 cm
Net weight	6.09 kg
Width	5.6 cm

### Input

[In] rated current	16 A
Permissible voltage	100...240 V
Input current limits	20 A
Load capacity	3300 VA
Network frequency	50/60 Hz
Plug standard	IEC 60320 C20
Input voltage	200 V 208 V 230 V

### Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



## Conformance

Product certifications	PSE UL listed VCCI class A VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003

## Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage altitude	0.00...15240.00 m

## Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------